



FMAX210SS

TANDEM SUPER SINGLE GOOSENECK

The FMAX210 Super Single does the kind of work other Single Wheel goosenecks only dream of.

25,000 lb GVWR

Available Sizes: 20' x 102", 22' x 102", 25' x 102", 28' x 102"
30' x 102", 32' x 102", 35' x 102", 38' x 102", 40' x 102"

STANDARD FEATURES

LOADING STYLE: 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

AXLES: 2 - 10,000 lb General Duty Electric Brake, Oil Bath

COUPLER: 25,000 lb Bulldog BX1

CROSS-MEMBERS: 3" Channel on 16" Centers w/Formed Gussets

FRAME: 16" Engineered Beam (Low Profile)

JACK: 2 - 12,000 lb Drop-Leg Jacks

NECK: 12" Engineered Neck

STAKE POCKETS: 2" x 3/8" Rub Rail w/ Stake Pockets & Pipe Spools

STORAGE: Diamond Plate Neck Box w/ Gas Shock Assisted Lid

SWAY CONTROL: Standard on 30' - 40' models

TIRES: ST235/75R17.5 18 Ply Radial, Super Single

DM COATING SYSTEM POWDER COAT

STANDARD COLORS									
	BLACK	WHITE	RED	CEMENT GRAY	METALLIC GRAY	METALLIC SILVER	METALLIC MOCHA	METALLIC BLUE	
SPECIAL COLORS									
	COMMERCIAL YELLOW	TRACTOR GREEN	INDUSTRIAL ORANGE	CUSTOM COLOR					

AVAILABLE WHEELS



SILVER (standard)



BLACK


POPULAR UPGRADES

- Electric-Over-Hydraulic Drum or Disc Brakes
- 3" Channel Cross-Members on 12" Centers w/Formed Gussets
- Blackwood Floor
- 2 - 10,000 lb Hydraulic Jacks
- 7'x 8' Weld-On/Bolt-On Deck on the Neck
- 14" x 14" x 36" Under-Slung Box

ENGINEERED TO DELIVER




U.S. Patent Protected



Tail Options


Straight Deck

With 8' slide-in ramps. Single piece bumper with light protection.




12' Hydraulic Dovetail

12' long with easy to climb, 12.5 degree approach angle. Blackwood rubber-infused runners for traction. Automatic latch for easy operation. Includes wireless remote control.



MAX Ramps

44" wide ramps for MAX versatility. 50 ksi steel ramp frames X 4 frames per ramp for MAX strength. HD Spring loaded for easy lifting from deck and from ground.



MAX Hinges

The two point ramp hinges are concealed and protected inside of the bumper like most. Our hinges transfer the force of the load into the knees of the ramps to prevent the back of the trailer from sagging and the ramps from kicking up when loading heavy equipment. For safe, stable loading.



Sealed Wiring Harness



LED Lights



Dexter Axles



Powder Coating Finish



Warranty Quality & Workmanship

LIGHTER. STRONGER. #DOWORK

For additional information visit:
www.diamondc.com/fleetneck

