

# PHOENIX



ALL NEW 3RD A/C OPTION  
(SELECT MODELS)

YOUR LOCAL DEALER



STANDARD  
WITH WEATHER  
SHIELD PLUS



SCAN HERE FOR ADDITIONAL PHOTOS, 360  
VIRTUAL TOURS, VIDEOS, & A COMPLETE  
LIST OF STANDARDS, OPTIONS & MORE!

[WWW.SHASTARVING.COM/FIFTH-WHEELS](http://WWW.SHASTARVING.COM/FIFTH-WHEELS)

SHASTA PHOENIX 5TH WHEELS





*Shasta* PHOENIX LITE



LIONSHEAD 5,2,1 GUARANTEE - 2 - USA-MADE DEXTER AXLES



*Shasta* PHOENIX MID-PROFILE



Silver Beach Decor - 3 - Mahogany Bay Decor



# LITE

Model	25RE	274BH	284RL	30RLS	30BH
Carrying Capacity (lbs)	2,527	2,308	2,592	2,019	1,965
UVW (lbs)	7,273	8,692	8,908	8,981	9,535
GVWR (lbs)	9,800	11,000	11,500	11,000	11,500
Hitch Weight (lbs)	1,115	1,420	1,434	1,445	1,553
Exterior Height (Factoring STD. A/C Only)	12'	12'	12'	12'	12'
Fresh Water Capacity (gal)	40	40	40	40	40
Grey Water Capacity (gal)	33	66	66	66	66
Waste Water Capacity (gal)	33	33	33	33	33
Awning Length	13'	16'	11'	11'	15'
Wheel Size	16"	16"	16"	16"	16"
Exterior Length (Includes Bumper to Cap)	29' 10"	35' 11"	34' 2"	34' 2"	37'
Interior Height (Coach)	81"	81"	81"	81"	81"
Axles Rating (lbs)	5,100	5,100	5,100	5,100	5,100
Tire Size	ST235/80R16E	ST235/80R16E	ST235/80R16E	ST235/80R16E	ST235/80R16E

HEIGHT FACTORS MAIN A/C ONLY (2ND A/C OPTIONAL)

# X-EDITION

Model	355FBX	393MBX
Carrying Capacity (lbs)	2,958	2,420
UVW (lbs)	11,542	13,080
GVWR (lbs)	14,500	15,500
Hitch Weight (lbs)	2,008	2,498
Exterior Height (Factoring STD. A/Cs Only)	13'	13'
Fresh Water Capacity (gal)	48	48
Grey Water Capacity (gal)	135	85
Waste Water Capacity (gal)	90	45
Awning Length	20'	20'
Wheel Size	16"	16"
Exterior Length (Includes Bumper to Cap)	42' 6"	42' 6"
Interior Height (Coach)	85"	85"
Axles Rating (lbs)	7,000	7,000
Tire Size	ST235/80R16G	ST235/80R16G

HEIGHT FACTORS 2ND 15K A/C (STANDARD)

# PHOENIX



**24/7 EMERGENCY  
ROADSIDE ASSISTANCE  
WITH VEHICLE PURCHASE\***

TOWING  
JUMP-STARTS  
TIRE CHANGES  
FLUID DELIVERY  
LOCKOUT  
SERVICE

WINCH-OUT  
MOBILE MECHANIC  
TECHNICAL  
SUPPORT  
DEALER LOCATOR  
SERVICES



\*VALID FOR 1 YEAR FROM DATE OF PURCHASE

# MID-PROFILE

Model	298RLS	334FL	336RL	360BH	367BH	370BAF	373MBRB
Carrying Capacity (lbs)	2,425	2,600	2,980	2,550	3,172	2,078	1,969
UVW (lbs)	9,575	12,400	10,520	11,450	12,328	12,422	13,031
GVWR (lbs)	12,000	15,000	13,500	14,000	15,500	14,500	15,000
Hitch Weight (lbs)	1,935	2,708	1,880	2,100	2,194	2,152	2,219
Exterior Height (Factoring STD. A/Cs Only)	13'	13'	13'	13'	13'	13'	13'
Fresh Water Capacity (gal)	48	48	48	48	48	48	48
Grey Water Capacity (gal)	90	85	90	90	112	112	120
Waste Water Capacity (gal)	45	45	45	45	72	72	75
Awning Length	15'	20'	16'	18'	15'	11'	17'
Wheel Size	16"	16"	16"	16"	16"	16"	16"
Exterior Length (Includes Bumper to Cap)	34' 8"	42' 6"	37'	39' 9"	42' 6"	42' 6"	42' 6"
Interior Height (Coach)	85"	85"	85"	85"	85"	85"	85"
Axles Rating (lbs)	5,100	7,000	7,000	7,000	7,000	7,000	7,000
Tire Size	ST235/80R16E	ST235/80R16G	ST235/80R16G	ST235/80R16G	ST235/80R16G	ST235/80R16G	ST235/80R16G

HEIGHT FACTORS 2ND 15K A/C (STANDARD)

CUSTOMER SATISFACTION



www.ForestRiverBuyLocal.com

GVWR (GROSS VEHICLE WEIGHT RATING) - IS THE MAXIMUM PERMISSIBLE WEIGHT OF THE UNIT WHEN FULLY LOADED. IT INCLUDES ALL WEIGHTS, INCLUSIVE OF ALL FLUIDS, CARGO, OPTIONAL EQUIPMENT AND ACCESSORIES. FOR SAFETY AND PRODUCT PERFORMANCE DO NOT EXCEED THE GVWR.

GVWR (GROSS AXLE WEIGHT RATING) - IS THE MAXIMUM PERMISSIBLE WEIGHT, INCLUDING CARGO, FLUIDS, OPTIONAL EQUIPMENT AND ACCESSORIES THAT CAN BE SAFELY SUPPORTED BY A COMBINATION OF ALL AXLES.

UVW (UNLOADED VEHICLE WEIGHT) - IS THE TYPICAL WEIGHT OF THE UNIT AS MANUFACTURED AT THE FACTORY. IT INCLUDES ALL WEIGHT AT THE UNIT'S AXLES AND TONGUE OR PIN AND LP GAS. THE UVW DOES NOT INCLUDE CARGO, FRESH POTABLE WATER, ADDITIONAL OPTIONAL EQUIPMENT OR DEALER INSTALLED ACCESSORIES. \*ESTIMATED AVERAGE BASED ON STANDARD BUILD OPTIONAL EQUIPMENT.

CCC (CARGO CARRYING CAPACITY) - IS THE AMOUNT OF WEIGHT AVAILABLE FOR FRESH POTABLE WATER, CARGO, ADDITIONAL OPTIONAL EQUIPMENT AND ACCESSORIES. CCC IS EQUAL TO GVWR MINUS UVW. AVAILABLE CCC SHOULD ACCOMMODATE FRESH POTABLE WATER (8.3 LBS PER GALLON). BEFORE FILLING THE FRESH WATER TANK, EMPTY THE BLACK AND GRAY TANKS TO PROVIDE FOR MORE CARGO CAPACITY.

\*\* ESTIMATED AVERAGE BASED ON STANDARD BUILD OPTIONAL EQUIPMENT. EACH FOREST RIVER RV IS WEIGHED AT THE MANUFACTURING FACILITY PRIOR TO SHIPPING. A LABEL IDENTIFYING THE UNLOADED VEHICLE WEIGHT OF THE ACTUAL UNIT AND THE CARGO CARRYING CAPACITY IS APPLIED TO EVERY FOREST RIVER RV PRIOR TO LEAVING OUR FACILITIES.

THE LOAD CAPACITY OF YOUR UNIT IS DESIGNATED BY WEIGHT, NOT BY VOLUME, SO YOU CANNOT NECESSARILY USE ALL AVAILABLE SPACE WHEN LOADING YOUR UNIT.

2023 COACHMEN RV  
A DIVISION OF FOREST RIVER, INC.  
A BERKSHIRE HATHAWAY COMPANY ALL RIGHTS RESERVED



Learn More  
Scan this barcode using  
a QR Reader on your  
smart phone to learn  
more about Forest River.



**PRE-DELIVERY INSPECTION FACILITY**  
20,000 square feet of quality assurance. The bare essentials for a premium product. This state-of-the-art facility gives immediate daily feedback to production for quality assurance in every unit built.

**AZDEL COMPOSITE  
SIDEWALL PANELS**



ALL INFORMATION CONTAINED IN THIS BROCHURE IS BELIEVED TO BE ACCURATE AT THE TIME OF PUBLICATION. HOWEVER, DURING THE MODEL YEAR IT MAY BE NECESSARY TO MAKE REVISIONS. FOREST RIVER, INC. RESERVES THE RIGHT TO MAKE ALL SUCH CHANGES WITHOUT NOTICE, INCLUDING PRICES, COLORS, MATERIALS, EQUIPMENT, AND SPECIFICATIONS, AS WELL AS THE ADDITION OF NEW MODELS AND THE DISCONTINUANCE OF MODELS SHOWN IN THIS BROCHURE. THEREFORE, PLEASE CONSULT WITH YOUR FOREST RIVER DEALER AND CONFIRM THE EXISTENCE OF ANY MATERIALS, DESIGN, OR SPECIFICATIONS THAT ARE MATERIAL TO YOUR PURCHASE DECISION. OPTIONAL EQUIPMENT IS NOT FACTORED IN UNIT SPECS. \* = WHERE APPLICABLE. (REV. 1-1-23)