



## 2025 NC750X DCT SPECIFICATIONS\*

### ENGINE

Engine Type	745cc liquid-cooled four-stroke 55° parallel-twin
Bore And Stroke	77.0mm x 80.0mm
Compression Ratio	10.7:1
Induction	Programmed Fuel Injection system (PGM-FI); 36.0mm throttle bodies
Valve Train	SOHC; four valves per cylinder

### DRIVETRAIN

Transmission	Six-speed automatic Dual-Clutch Transmission
Final Drive	#520 Chain; 17T/41T

### CHASSIS SUSPENSION BRAKES

Front Suspension	41.0mm Showa® telescopic fork; 4.7-inch travel
Rear Suspension	Pro-Link® single shock; 4.7-inch travel
Front Brake	Dual 296.0mm discs; 2-channel ABS
Rear Brake	Single 240.0mm disc; 2-channel ABS
Front Tire	120/70ZR-17 radial
Rear Tire	160/60ZR-17 radial

### DIMENSIONS

Rake	27.0°
Trail	4.3 inches
Wheelbase	60.3 inches
Seat Height	31.6 inches
Curb Weight	497 pounds (Includes all standard equipment, required fluids and full tank of fuel—ready to ride)
Fuel Capacity	3.7 gallons

### OTHER

Model ID	NC750XD
Emissions	Meets current EPA and California Air Resources Board (CARB) standards.
Available Colors	Matte Pearl White

### FACTORY WARRANTY INFORMATION

Duration	Transferable, one year included, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

\*All figures are preliminary and subject to change.