



## 2025 PCX SPECIFICATIONS\*

### ENGINE

Engine Type	157cc liquid-cooled 80° single-cylinder four-stroke
Bore And Stroke	60.0mm x 55.5mm
Compression Ratio	12.0:1
Valve Train	SOHC; four valves per cylinder
Induction	Programmed Fuel-Injection system (PGM-FI); 28.0mm throttle body

### DRIVETRAIN

Transmission	Automatic V-Matic belt drive
--------------	------------------------------

### CHASSIS SUSPENSION BRAKES

Front Suspension	31.0mm telescopic fork; 3.9-inch travel
Rear Suspension	Twin hydraulic shock absorbers; 3.7-inch travel
Front Brake	Single 220.0mm disc; front-wheel ABS
Rear Brake	Rod-actuated 130.0mm drum
Front Tire	110/70-14
Rear Tire	130/70-13

### DIMENSIONS

Rake	26.5°
Trail	3.1 inches
Seat Height	30.1 inches
Wheelbase	51.7 inches
Curb Weight	291 pounds (Includes all standard equipment, required fluids and a full tank of fuel--ready to ride)
Fuel Capacity	2.1 gallons

### OTHER

Model ID	PCX160A
Available Colors	Pearl Gray

### FACTORY WARRANTY INFORMATION

Duration	Transferable, one year included, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

\*All figures are preliminary and subject to change.