



2025 PIONEER 1000-6 DELUXE CREW SPECIFICATIONS*

ENGINE

Engine Type	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke
Bore And Stroke	92.0mm x 75.2mm
Valve Train	Unicam® SOHC; four valves per cylinder
Compression Ratio	10.0:1
Induction	Programmed Fuel injection system (PGM-FI); 44.0mm throttle body

DRIVETRAIN

Transmission	Fully automatic Dual-Clutch Transmission (DCT)
Driveline	Direct front and rear driveshafts

CHASSIS SUSPENSION BRAKES

Front Suspension	Independent double-wishbone; 10.5-inch travel
Rear Suspension	Independent double-wishbone; 10.0-inch travel
Front Brakes	Dual 210.0mm hydraulic discs
Rear Brakes	Dual 210.0mm hydraulic discs
Front Tires	27 x 9-14
Rear Tires	27 x 11-14

DIMENSIONS

Length	152.2 inches
Width	63.0 inches
Height	76.1 inches
Wheelbase	115.2 inches
Bed Capacity	1000.0 pounds (49-state models); 600.0 pounds (CA model)
Towing Capacity	2500.0 pounds
Ground Clearance	12.6 inches
Turning Radius	18.7 feet
Curb Weight	1936 pounds - Includes all standard equipment, required fluids and full tank of fuel.
Fuel Capacity	7.9 gallons, including 1.7-gallon reserve

OTHER

Safety	Recommended for Drivers 16 years of age and older.
Available Colors	Hero Red, Black Forest Green, TrueTimber® Atera Camo
Model ID	SxS10M6D
Seating Capacity	6

FACTORY WARRANTY INFORMATION

Duration	Transferable, one year included, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.