



GO ANYWHERE, EVERY TIME

The original, and still the adventure touring standard, our Africa Twin is the go-anywhere Honda. Each model pairs a potent 1084cc Unicam® engine with real-world comfort and available DCT. Choose the standard model with its 21-inch front wheel to journey deeper off-road, or opt for the Africa Twin Adventure Sports ES with electronic suspension and 19-inch front wheel for improved on-road performance. Never stop exploring.

ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING. NEVER RIDE AFTER CONSUMING DRUGS OR ALCOHOL, AND NEVER USE THE STREET AS A RACETRACK. RESPECT THE ENVIRONMENT WHEN RIDING. Africa Twin® is a registered trademark of Honda Motor Co., Ltd. Pro-Link® is a registered trademark of Showa Mtg., Inc. Apple CarPlay and iPhone are trademarks of Apple Inc. For using Apple CarPlay, connection to a commercially available Bluetooth headset is necessary. See owner's manual for Bluetooth headset requirements. Unicam® and Pro-Link® are registered trademarks of Honda Motor Co ©2026 American Honda Motor Co., Inc



2026 Africa Twin/ Adventure Sports ES



Africa Twin/DCT



MATTE BLACK METALLIC
PEARL WHITE

Africa Twin Adventure Sports ES/DCT



PEARL WHITE

FEATURES & BENEFITS

1084cc TWIN-CYLINDER ENGINE

Our narrow 1084cc Unicam® parallel-twin engine delivers torque smoothly throughout the rpm range, making it great for everything from off-road riding to all-day highway cruising.

TIRES & WHEELS

All Africa Twin models have wire-spoked wheels. The standard models feature 21-inch front and 18-inch rear wheels designed for better off-road performance, while the Adventure Sports ES models get a more road-focused 19-inch front wheel and wider rims.

LOW CENTER OF GRAVITY

By placing heavy components like the battery near the bike's center of gravity and using a compact engine, we've created a platform for excellent handling.

Apple CarPlay™ AND ANDROID AUTO™

All Africa Twin models have wire-spoked wheels. The standard models feature 21-inch front and 18-inch rear wheels designed for better off-road performance, while the Adventure Sports ES models get a more road-focused 19-inch front wheel and wider rims.





2026 Africa Twin Africa Twin Adventure Sports ES



Africa Twin



Africa Twin Automatic DCT

ENGINE TYPE	1084cc liquid-cooled parallel-twin four-stroke	1084cc liquid-cooled parallel-twin four-stroke
BORE AND STROKE	92.0mm x 81.5mm	92.0mm x 81.5mm
INDUCTION	Programmed Fuel Injection (PGM-FI); 46mm throttle body	Programmed Fuel Injection (PGM-FI); 46mm throttle body
VALVE TRAIN	Unicam SOHC; four valves per cylinder	Unicam SOHC; four valves per cylinder
COMPRESSION RATIO	10.5:1	10.5:1
TRANSMISSION	6-speed manual	Six-speed automatic Dual-Clutch Transmission (DCT)
FINAL DRIVE	#525 Chain; 16T/42T	#525 Chain; 16T/42T
FRONT SUSPENSION	45mm inverted Showa SFF-BP fork; 9.1 inches of travel	45mm inverted Showa SFF-BP fork; 9.1 inches of travel
REAR SUSPENSION	Pro-Link® Showa single shock; 8.7 inches of travel	Pro-Link Showa single shock; 8.7 inches of travel
FRONT BRAKES	Dual 310mm discs with four-piston calipers; ABS	Dual 310mm discs with radial-mounted four-piston calipers; ABS
REAR BRAKES	Single 256mm disc with single-piston caliper; ABS	Single 256mm disc with single-piston caliper; ABS
FRONT TIRES	90/90-21	90/90-21
REAR TIRES	150/70R-18	150/70R-18
RAKE	27°	27°
TRAIL	4.5 inches	4.5 inches
WHEELBASE	62.0 inches	62.0 inches
SEAT HEIGHT	34.3 inches (standard position)/33.5 inches (low position)	34.3 inches (standard position)/33.5 inches (low position)
CURB WEIGHT	510 lbs—Includes all standard equipment, required fluids and full tank of fuel	535 lbs—Includes all standard equipment, required fluids and full tank of fuel
FUEL CAPACITY	5.0 gallons	5.0 gallons



2026 Africa Twin Africa Twin Adventure Sports ES



Africa Twin Adventure Sports ES



Africa Twin Adventure Sports ES DCT

ENGINE TYPE	1084cc liquid-cooled parallel-twin four-stroke	1084cc liquid-cooled parallel-twin four-stroke
BORE AND STROKE	92.0mm x 81.5mm	92.0mm x 81.5mm
INDUCTION	Programmed Fuel Injection (PGM-FI); 46mm throttle body	Programmed Fuel Injection (PGM-FI); 46mm throttle body
VALVE TRAIN	Unicam SOHC; four valves per cylinder	Unicam SOHC; four valves per cylinder
COMPRESSION RATIO	10.5:1	10.5:1
TRANSMISSION	Six-speed manual	Six-speed manual
FINAL DRIVE	#525 Chain; 16T/42T	#525 Chain; 16T/42T
FRONT SUSPENSION	45mm inverted Showa EERA® fork with electronic adjustment; 8.3 inches of travel	45mm inverted telescopic fork with electronic adjustment; 8.3 inches of travel
REAR SUSPENSION	Pro-Link Showa single shock with electronic adjustment; 7.9 inches of travel	Pro-Link Showa single shock with electronic adjustment; 7.9 inches of travel
FRONT BRAKES	Dual 310mm discs with radial-mounted four-piston calipers; ABS	Dual 310mm discs with radial-mounted four-piston calipers; ABS
REAR BRAKES	Single 256mm disc with single-piston caliper; ABS	Single 256mm disc with single-piston caliper; ABS
FRONT TIRES	110/80-19	110/80-19
REAR TIRES	150/70R-18	150/70R-18
RAKE	27°	27°
TRAIL	4.2 inches	4.2 inches
WHEELBASE	61.8 inches	61.8 inches
SEAT HEIGHT	33.7 inches (standard position)/32.9 inches (low position)	33.7 inches (standard position)/32.9 inches (low position)
CURB WEIGHT	535 lbs—Includes all standard equipment, required fluids and full tank of fuel	559 lbs—Includes all standard equipment, required fluids and full tank of fuel
CURB WEIGHT	6.6 gallons including	6.6 gallons including