



# EVERY CHAMPION STARTS SOMEWHERE

A great place to start. An even better place to win. The CRF150R and CRF150RB Expert are built for young motocross racers, with high-revving Unicam® engines and race-proven components. The Expert adds larger wheels for a taller seat height—perfect for growing riders chasing bigger goals. However far they're going, it all starts here.



CRF150R/EXPERT IS INTENDED FOR CLOSED-COURSE OPERATION ONLY. ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING, AND PLEASE RESPECT THE ENVIRONMENT. OBEY THE LAW AND READ THE OWNER'S MANUAL THOROUGHLY. Showa® is a registered trademark of Showa Mfg., Inc. CRF®, Unicam® and Pro-Link® are registered trademarks of Honda Motor Co., Ltd. ©2024 American Honda Motor Co., Inc.

# 2026 CRF150R/Expert



**CRF150R**



**CRF150RB Expert**



## **FEATURES & BENEFITS**

### **UNICAM ENGINE**

The CRF150R uses a Unicam engine based on our championship-winning CRF450R. Designed to give you excellent rideability and more power and torque across the rev range, the engine runs consistently at different tracks — it's an all-around winner.

### **ACCELERATOR PUMP**

The CRF150R uses a carburetor featuring a “direct push” accelerator pump which gives you better, more immediate throttle response.

### **TRACK-DESIGNED CHASSIS**

A lightweight, high-tensile steel frame with large-diameter frame tubing and crossmember delivers excellent turning performance and straight-line tracking.

### **FRONT AND REAR DISC BRAKES**

Front and rear disc brakes provide powerful, precise stopping power.





# 2026 CRF150R/ CRF150RB Expert



CRF150R



CRF150RB Expert

<b>ENGINE TYPE</b>	150cc liquid-cooled single-cylinder	150cc liquid-cooled single-cylinder
<b>BORE AND STROKE</b>	66.0mm x 43.8mm	66.0mm x 43.8mm
<b>INDUCTION</b>	32mm Keihin flat-slide carburetor with Throttle Position Sensor (TPS)	32mm Keihin flat-slide carburetor with Throttle Position Sensor (TPS)
<b>VALVE TRAIN</b>	Unicam SOHC; four valves per cylinder	Unicam SOHC; four valves per cylinder
<b>COMPRESSION RATIO</b>	11.7:1	11.7:1
<b>FINAL DRIVE</b>	#420 chain; 15T/50T	#420 chain; 15T/56T
<b>TRANSMISSION</b>	Close-ratio five-speed	Close-ratio five-speed
<b>FRONT SUSPENSION</b>	37mm leading-axle inverted Showa® fork; 10.8-inch travel	37mm leading-axle inverted Showa fork; 10.8-inch travel
<b>REAR SUSPENSION</b>	Pro-Link® Showa single shock; 10.7-inch travel	Pro-Link Showa single shock; 10.7-inch travel
<b>FRONT BRAKE</b>	Single 220mm disc	Single 220mm disc
<b>REAR BRAKE</b>	Single 190mm disc	Single 190mm disc
<b>FRONT TIRE</b>	Dunlop MX51; 70/100-17	Dunlop MX51; 70/100-19
<b>REAR TIRE</b>	Dunlop MX51; 90/100-14	Dunlop MX51; 90/100-16
<b>RAKE</b>	27.0°	27.8°
<b>TRAIL</b>	3.1 inches	3.8 inches
<b>WHEELBASE</b>	49.6 inches	50.6 inches
<b>SEAT HEIGHT</b>	32.8 inches	34.1 inches
<b>GROUND CLEARANCE</b>	11.9 inches	13.2 inches
<b>CURB WEIGHT</b>	185 pounds (Includes all standard equipment, required fluids and a full tank of fuel)	187 pounds (Includes all standard equipment, required fluids and a full tank of fuel)
<b>FUEL CAPACITY</b>	1.1 gallons	1.1 gallons