



2026 FOURTRAX RANCHER 4X4 AUTOMATIC DCT IRS EPS SPECIFICATIONS*

ENGINE

Engine Type	420cc longitudinally mounted liquid-cooled wet-sump single-cylinder four-stroke
Bore And Stroke	86.5mm x 71.5mm
Compression Ratio	9.9:1
Valve Train	OHV; two valves per cylinder
Induction	Programmed Fuel Injection system (PGM-FI); 34.0mm throttle body
Starter	Electric with optional auxiliary recoil

DRIVETRAIN

Clutch	Automatic
Transmission	Five-speed automatic Dual-Clutch Transmission (DCT) with reverse
Driveline	Direct front and rear driveshafts with torque-sensitive locking front differential

CHASSIS SUSPENSION BRAKES

Front Suspension	Independent double-wishbone; 7.3-inch travel
Rear Suspension	Independent dual-arm; 8.5-inch travel
Front Brakes	Dual 193.0mm discs
Rear Brake	170.0mm disc
Front Tires	24 x 8-12
Rear Tires	24 x 10-12

DIMENSIONS

Length	84.5 inches
Width	47.4 inches
Height	47.2 inches
Wheelbase	51.0 inches
Seat Height	35.4 inches
Ground Clearance	9.6 inches
Curb Weight	686 pounds (includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	3.9 gallons, including 1.3-gallon reserve
Turning Radius	11.5 feet
Front Rack Capacity	66.0 pounds
Rear Rack Capacity	133.0 pounds

OTHER

Model ID	TRX420FA6
Emissions	Meets current EPA and CARB (California) off-road emissions standards.
Available Colors	Hero Red, Blue, TrueTimber® Atera Camo
Important Safety Information	Recommended for riders 16 years of age and older. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.

FACTORY WARRANTY INFORMATION

Duration	Transferable, one year included, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.

©2025 American Honda Motor Co., Inc. – Powersports Division