



2026 FOURTRAX RANCHER 4X4 SPECIFICATIONS*

ENGINE

Engine Type	420cc longitudinally mounted liquid-cooled single-cylinder four-stroke
Bore And Stroke	86.5mm x 71.5mm
Compression Ratio	9.9:1
Valve Train	OHV; two valves per cylinder
Induction	Programmed Fuel Injection system (PGM-FI); 34.0mm throttle body
Starter	Electric with optional auxiliary recoil

DRIVETRAIN

Clutch	Automatic
Transmission	Five-speed manual with reverse
Driveline	Direct front and rear driveshafts with torque-sensitive locking front differential

CHASSIS SUSPENSION BRAKES

Front Suspension	Independent double-wishbone; 6.7-inch travel
Rear Suspension	Swingarm with single shock; 6.7-inch travel
Front Brakes	Dual 190.0mm discs
Rear Brake	160.0mm sealed mechanical drum
Front Tires	24 x 8-12
Rear Tires	24 x 10-11

DIMENSIONS

Length	82.8 inches
Width	47.4 inches
Height	46.2 inches
Wheelbase	50.0 inches
Seat Height	33.6 inches
Ground Clearance	7.1 inches
Curb Weight	615 pounds (includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	3.9 gallons, including 1.3-gallon reserve
Turning Radius	9.2 feet
Front Rack Capacity	66.0 pounds
Rear Rack Capacity	133.0 pounds

OTHER

Model ID	TRX420FM1
Emissions	Meets current EPA and CARB (California) off-road emissions standards.
Available Colors	Hero Red, Black Forest Green, TrueTimber® Atera Camo
Important Safety Information	Recommended for riders 16 years of age and older. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.

FACTORY WARRANTY INFORMATION

Duration	Transferable, one year included, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.

©2025 American Honda Motor Co., Inc. – Powersports Division