



TOURING'S GOLD STANDARD

There are over four million miles of roads in the United States, and some of them lead to spectacular destinations. Some wander through picturesque small towns. Some cross majestic mountains, and others roll through the heartland. But each one offers a delight all its own — especially if you're on a motorcycle. Our Gold Wing Tour is a proven travelling companion, ready to carry you and a lucky passenger wherever your heart leads you, all in comfort, refinement, and a proven legacy of performance. Four million miles — isn't it time you got started?

ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING. NEVER RIDE AFTER CONSUMING DRUGS OR ALCOHOL, AND NEVER USE THE STREET AS A RACETRACK. RESPECT THE ENVIRONMENT WHEN RIDING. Gold Wing® is a registered trademark of Honda Motor Co., Ltd. Apple CarPlay and iPhone are trademarks of Apple Inc. For using Apple CarPlay, connection to a commercially available Bluetooth headset is necessary. See owner's manual for Bluetooth headset requirements. ©2026 American Honda Motor Co., Inc



2026 Gold Wing Tour/ Automatic DCT/Airbag



FEATURES & BENEFITS

ENGINE

The horizontally opposed six-cylinder engine is famously smooth and powerful. The latest version is an 1833cc design that's over 13 pounds lighter than previous generations (more than eight pounds less for our DCT trims). *Standard on: all trims.*

Gold Wing Tour



Gold Wing Tour Automatic DCT



Gold Wing Tour Airbag Automatic DCT



SEVEN-SPEED AUTOMATIC DCT

Available with our revolutionary seven-speed automatic Dual-Clutch Transmission (DCT), the shifts are fast and smooth, and the overdrive seventh gear is perfect for highway cruising. *Standard on: Gold Wing Tour Automatic DCT & Gold Wing Tour Airbag DCT*

APPLE CARPLAY™ WIRELESS CONNECTIVITY

Apple's CarPlay™* seamlessly integrates your iPhone®* into your bike. Available Bluetooth®**-enabled wireless headsets let you communicate more easily than ever.

DOUBLE-WISHBONE FRONT SUSPENSION

The radical double-wishbone front suspension delivers stellar handling and gives the bike a sleek, sporty appearance. The innovative design changes the wheel's path, letting us move both the engine and rider/passenger closer to the front wheel. *Standard on: all trims.*





2025 Gold Wing Tour/ Automatic DCT/ Airbag



Gold Wing Tour



Gold Wing Tour Automatic DCT



Gold Wing Tour DCT Airbag

| | Gold Wing Tour | Gold Wing Tour Automatic DCT | Gold Wing Tour DCT Airbag |
|--------------------------|---|---|---|
| ENGINE TYPE | 1833cc liquid-cooled horizontally opposed six-cylinder four-stroke | 1833cc liquid-cooled horizontally opposed six-cylinder four-stroke | 1833cc liquid-cooled horizontally opposed six-cylinder four-stroke |
| BORE AND STROKE | 73.0mm x 73.0mm | 73.0mm x 73.0mm | 73.0mm x 73.0mm |
| INDUCTION | Programmed Fuel Injection (PGM-FI); 50mm throttle body | Programmed Fuel Injection (PGM-FI); 50mm throttle body | Programmed Fuel Injection (PGM-FI); 50mm throttle body |
| VALVE TRAIN | Unicam SOHC; four valves per cylinder | Unicam SOHC; four valves per cylinder | Unicam SOHC; four valves per cylinder |
| COMPRESSION RATIO | 10.5:1 | 10.5:1 | 10.5:1 |
| TRANSMISSION | Six-speed manual plus reverse and walking mode | Seven-speed automatic DCT; plus reverse and walking mode | Seven-speed automatic DCT; plus reverse and walking mode |
| FINAL DRIVE | Shaft | Shaft | Shaft |
| FRONT SUSPENSION | Double wishbone; 4.3 inch-travel | Double wishbone; 4.3 inch-travel | Double wishbone; 4.3 inch-travel |
| REAR SUSPENSION | Pro Arm® single-sided swingarm with Pro-Link® single shock; 4.1 inch-travel | Pro Arm single-sided swingarm with Pro-Link single shock; 4.1 inch-travel | Pro Arm single-sided swingarm with Pro-Link single shock; 4.1 inch-travel |
| FRONT BRAKES | Dual 320mm discs | Dual 320mm discs ABS | Dual 320mm discs |
| REAR BRAKE | Single 316mm disc | Single 316mm disc | Single 316mm disc |
| FRONT TIRES | 130/70-18 | 130/70-18 | 130/70-18 |
| REAR TIRES | 200/55-16 | 200/55-16 | 200/55-16 |
| RAKE | 30.5° | 30.5° | 30.5° |
| TRAIL | 4.3 inches | 4.3 inches | 4.3 inches |
| WHEELBASE | 66.9 inches | 66.9 inches | 66.9 inches |
| SEAT HEIGHT | 29.3 inches | 29.3 inches | 29.3 inches |
| CURB WEIGHT | 845 pounds (Includes all standard equipment, required fluids and full tank of fuel) | 847 pounds (Includes all standard equipment, required fluids and a full tank of fuel) | 856 pounds (Includes all standard equipment, required fluids and a full tank of fuel) |
| FUEL CAPACITY | 5.5 gallons | 5.5 gallons | 5.5 gallons |