



MOST FUN YOU CAN HAVE ON TWO WHEELS

Big fun can come in a small package, and the Honda Grom proves it. With its perfect mix of size, power, and style, every ride is a blast. Three trim options and customizable body panels let you make it your own—because urban adventure is better when it looks as fun as it feels.



2026 Grom/ABS/SP

ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING. NEVER RIDE AFTER CONSUMING DRUGS OR ALCOHOL, AND NEVER USE THE STREET AS A RACETRACK. Grom® is a registered trademark of Honda Motor Co., Ltd. ©2024 American Honda Motor Co., Inc.



FEATURES & BENEFITS

124cc FUEL-INJECTED ENGINE

Nobody can match our reputation for engines. Despite its compact size, the Grom offers exceptional performance and reliability.

LOW SEAT HEIGHT

With a seat height of only 30 inches, most riders can easily flat-foot it in parking lots or at stop lights. The seat is also thickly padded for added comfort, especially for taller riders.

DISC BRAKES

Hydraulic disc brakes measuring 220mm at the front and 190mm at the rear come standard, providing exceptional stopping power

CUSTOMIZABLE BODYWORK

With the Grom, style is the name of the game. One of the main benefits of its unique design is that it can be easily customized by replacing the bodywork with various options from our accessory line.



Grom



PEARL WHITE

CHERRY RED

CANDY BLUE



Grom ABS



PEARL WHITE



Grom SP



MATTE BLACK METALLIC





2026 Grom /SP/ABS



Grom



Grom SP



Grom ABS

ENGINE TYPE	124cc liquid-cooled single-cylinder four-stroke	124cc liquid-cooled single-cylinder four-stroke	124cc liquid-cooled single-cylinder four-stroke
BORE AND STROKE	50.0mm x 63.1mm	50.0mm x 63.1mm	50.0mm x 63.1mm
INDUCTION	Programmed fuel injection (PGM-FI); 24mm throttle body	Programmed fuel injection (PGM-FI); 24mm throttle body	Programmed fuel injection (PGM-FI); 24mm throttle body
VALVE TRAIN	SOHC; two valves per cylinder	SOHC; two valves per cylinder	SOHC; two valves per cylinder
COMPRESSION RATIO	10:1	10:1	10:1
TRANSMISSION	Five-speed manual	Five-speed manual	Five-speed manual
FINAL DRIVE	#420 Chain; 15T/38T	#420 Chain; 15T/38T	#420 Chain; 15T/38T
FRONT SUSPENSION	31mm inverted fork; 3.9-inch travel	31mm inverted fork; 3.9-inch travel	31mm inverted fork; 3.9-inch travel
REAR SUSPENSION	Single shock; 4.1-inch travel	Single shock; 4.1-inch travel	Single shock; 4.1-inch travel
FRONT BRAKES	Single 220mm disc	Single 220mm disc	Single 220mm disc; ABS
REAR BRAKES	Single 190mm disc	Single 190mm disc	Single 190mm
FRONT TIRES	120/70-12	120/70-12	120/70-12
REAR TIRES	130/70-12	130/70-12	130/70-12
RAKE	25°	25°	25°
TRAIL	3.3 inches	3.3 inches	3.3 inches
WHEELBASE	47.2 inches	47.2 inches	47.2 inches
SEAT HEIGHT	30.0 inches	30.0 inches	30.0 inches
CURB WEIGHT	224 pounds (Includes all standard equipment, required fluids and full tank of fuel)	224 pounds (Includes all standard equipment, required fluids and full tank of fuel)	227 pounds (Includes all standard equipment, required fluids and a full tank of fuel)
FUEL CAPACITY	1.6 gallons	1.6 gallons	1.6 gallons