

TECHNICAL SPECIFICATIONS

2027 KTM 65 SX

ENGINE

Design	1-CYLINDER, 2-STROKE ENGINE
Displacement	64.9 CM ³
Transmission	6-SPEED
EMS	MIKUNI VM 24
Engine oil	MOTOREX TOPSPEED 4T 15W50
Clutch primary drive teeth	75
Primary drive	23:75
Clutch	WET, MULTI-DISC CLUTCH, FORMULA HYDRAULICS
Engine cylinder	SINGLE CYLINDER
Engine stroke	2-STROKE

CHASSIS

Frame design	CENTRAL-TUBE FRAME WITH DOUBLE-CRADLE
--------------	--

Front brake	DISC BRAKE
-------------	-------------------

Rear brake	DISC BRAKE
------------	-------------------

Rear subframe design	STEEL / POLYAMIDE GLASS FIBER
----------------------	--------------------------------------

Chain	420
-------	------------

SUSPENSION

Front suspension	XACT 35 WP UPSIDE-DOWN FORK, Ø 35 MM
------------------	---

Rear suspension	XACT WP MONO SHOCK
-----------------	---------------------------

Suspension travel (front)	215 MM
---------------------------	---------------

Suspension travel (rear)	253.5 MM
--------------------------	-----------------

Front suspension adjustment	COMPRESSION AND REBOUND ADJUSTABLE
-----------------------------	---

Rear suspension adjustment	COMPRESSION AND REBOUND ADJUSTABLE
----------------------------	---

DIMENSIONS

Seat height	730 MM
-------------	---------------

Ground clearance	259 MM
------------------	---------------

Tank capacity (approx.)	4.5 L
-------------------------	--------------

Weight (without fuel)	54.3 KG
-----------------------	----------------